

SQUALO TOP







Available in 2 standard lengths, or built-to-order in custom length.

- 3 HP engine, direct-on-disc
- 100% Aluminium table chassis and covers
- Stainless steel head rails and adjustable armoured ball bearings
- Polyethylene water basin with screw-in cap
 Weter goding system feeturing armoured.
- Water cooling system featuring armoured pipe, metallic tap and bilateral blade spray terminals
- Magnetic-induction pump
- PVC cable/pipe protection chain
- Cutting head's vertical tilt system allows for cut depth adjusting
- Cutting system's side tilt capability eases up to 45° ("mitre") cut
- Front, back and bilateral side blade protection devices included
- Electrical system featuring magneto thermal protection and release coil
- Retractable legs include fall-protection device
- Table handles and transport wheels included
- Supports \varnothing 250 and \varnothing 300 blades



		ART	•	kW	Нр	(RPM)	O _{mm}	om	om	Com		Double Cut of	Kg	(G)	↓ jom.
	SqualoTOP 100	1113	230V	2,2	3	2800	250	91	103	64x64	4.5	6	56	1	150x55xh80
	oqualo i oi i i o	1110	2001	2,2	0	2000	300	90	105	64x64	6	6	00		100,000,1100
	SqualoTOP 130	1114	230V	2,2	3	2800	250 300	121 120	133 135	84x84 84x84	4.5 6	6	59	1	180x55xh80
THELY CE							000	120	100	POATO	J	5			

ITALIAN MANUFACTURER

Machinery and tools for professional tilers and bricklayers