

SQUALO MAX







Available in 3 standard lengths, or built-to-order in custom length.

- 2 HP engine, direct-on-disc
- 100% Aluminium table chassis and covers
- Stainless steel head rails and adjustable armoured ball bearings
- Polyethylene water basin with screw-in cap
 Water seeling system feeturing armoured.
- Water cooling system featuring armoured pipe, metallic tap and bilateral blade spray terminals
- Magnetic-induction pump
- PVC cable/pipe protection chain
- Cutting head's vertical tilt system allows for cut depth adjusting
- Cutting system's side tilt capability eases up to 45° ("mitre") cut
- Front, back and bilateral side blade protection devices included
- Electrical system featuring magneto thermal protection and release coil
- Retractable legs include fall-protection device
- Table handles and transport wheels included
- Supports \varnothing 250 and \varnothing 300 blades



		ART	•	kW	Нр	(RPM)	⊙ _{mm}	om	om	₽ om		Double Cut of	Kg	(6)	↓om.
	SqualoMAX	1141	230V	1,5	2	2800	250 300	61 60	73 60	42x42 42x42	4.5 6	6	52	1	120x65xh80
	SqualoMAX 100	1142	230V	1,5	2	2800	250 300	91 90	103 90	64x64 64x64	4.5 6	6	55	1	150x65xh80
CE	SqualoMAX 130	1143	230V	1,5	2	2800	250 300	121 120	133 120	84x84 84x84	4.5 6	6	58	1	180x65xh80

ITALIAN MANUFACTURER

Machinery and tools for professional tilers and bricklayers