multipurpose square edge profile



SQUAREJOLLY SJ is a multipurpose aluminium profile suitable for many different situations arising in thin bed adhesive tile coverings.

This special 'symmetrical square' profile is recommended for multiple finishing effects.

In the drawing "H" corresponds to the tile thickness and "L"= H+1 mm to the visible part.

Anchorage improved on vertical side with the "dovetail" internal cavity. Patented system.

Illustrated scale dimension 1:1

- Junction of floors at the same level
- Decorative listellos
- Finishing the outer edges of wall tiles
- Entrance mat framing
- Upper finish of tiled skirting and edges
- Stair nosing profiles



squarejolly[™] SJ





SQUAREJOLLY SJ-IL Polished Stainless Steel AISI 304 - DIN 1.4301 and AISI 316

This stainless steel profile is AISI 304 standard which ensures high tolerance to most of diluted chemicals found in laboratories or strong detergents present in food processing plants, commercial kitchens, slaughter houses, breweries, hospitals, public toilets etc. The profile has a slight difference in shape compared to the brass one, due to the steel bending process. Available in top brushed effect, code IS.

SQUAREJOLLY SJ-AS Silver Anodised Aluminium

This profile has a silver coating and is suitable for both indoor or outdoor application with high tolerance to weather agents but less to mechanical impact. During installation, excess adhesive and grout should be removed immediately to avoid stains. The exposed surface may change colour or darken in time. Where higher stresses are involved the use of brass or stainless steel profiles is recommended.

8	SJ	80	IL
9	SJ	90	IL
10	SJ	100	IL
11	SJ	110	IL
12,5	SJ	125	IL
15	SJ	150	IL
H=mm		Art.	
8	SJ	80	AS
9	SJ	90	AS
10	SJ	100	AS
11	SJ	110	AS
	▲ 9 ▲ 10 ▲ 11 ▲ 12,5 ▲ 15 H=mm 8 9 10	▲ 9 SJ ▲ 10 SJ ▲ 11 SJ ▲ 12,5 SJ ▲ 15 SJ H=mm 8 SJ 9 SJ 10 SJ	

on vertical side



H=mm

12,5

Art.

SJ 125 AS



The profile inner section has been conceived to match with a special cap SQUARECAPSULE SJC which can work as external, internal, three-way junction and end-cap. All these functions with one piece.



SQUAREJOLLY SJ-ON Natural Brass

This brass profile is developed with prime choice raw material in order to guarantee tolerance and endurance to chemical and mechanical solicitations. Through contact with moisture or corrosive media, brass may oxidize on exposed surfaces. This situation can be easily solved by buffing the product with a conventional polisher to return to its original shine.

SQUARECAPSULE SJC*

The profile inner section has been conceived to match with a special cap which can work as external, internal, three-way junction and end-cap. All these functions with one piece.

CURVELINE

Some profiles of SQUAREJOLLY SJ series are also available with a special cut flange so they become formable for curved edges and inlays. To order: add the letter D to the product code.

Material: Extruded Natural brass Length: 2,70 metres Anchorage improved on vertical side

Art.		
SJ 80 ON		
SJ 100 ON		
SJ 125 ON		

		/
Material:	8 SJ(C 80
Aluminium/Brass/Stainless steel	9 SJ(C 90
	10 SJ(C 100
	11 SJ(C 110

H-mm

12,5

15



Art.

SJC 125 *

SJC 150 *